



DIMENSIONS



TOP VIEW



SIDE VIEW




BOTTOM VIEW




Straight Feed



TOP VIEW



SIDE VIEW




BOTTOM VIEW




Left Side Feed

TOP VIEW




SIDE VIEW



Bottom Feed is not available for FLXible Neon 1 Dual


BOTTOM VIEW



FLXible Neon can be cut every 50mm (1.97).


Please follow the cutting point mark to cut precisely as needed.

BEAM SPREADS




FN1 SC-24V-1M
45.2 lm/W
867 lm

INSTALLATION – Bracket




INSTALLATION – Field Termination (IP65)

* Components



* Expanded View




COMPONENTS



FLXible Neon 1
__FN1-SC-24V-5m(16.4)
__FN1-SC-24V-2m(6.6)



Expanding Stick
__FN-EPS



LED Drivers*
With distributor and power cord 1800mm (6)
__ FLC30-24V/XL
__ FLC75-24V/XL




Mounting Brackets
__FN1-BRACKET1



Field Termination
IP65
FN1-FTKIT-DUAL



Hard Wire Driver*
(90V to 300V)
__XLD200-224V-FCL-DIM
__XLD75-124V-FC



FN2 Extrusion Line
__FN1-EXL (4)



Control Interface –
FDD-L20
Max. 200W(100W/CH 2CH)
Required for dim to warm and tunable white

***A larger selection of drivers are available including remote and hard wire drivers. Please consult factory.**