

EcoSlimLamp LED



EcoSlimLamp

LED efficiency for cove, under cabinet and mil work at a fluorescent price !



Product Features

- AC power driver built in (SMPS not needed)
- Dark spot free at the linking point
- Round Milky diffuser
- Class I


Specification

- Frequency range : 60Hz
- Voltage : AC 120V
- Operating temperature : 0~45 °C
- Lamp life : 50,000Hr
- Energy efficiency : 75 lm/W
- Available color : 3000K, 3500K, 4000K, 6000K
- Color rendering : Ra > 80
- Degree of protection : IP 20

Notice




- Max connection : 400W
5W(72 pcs), 10W(40 pcs), 15W(26 pcs), 20W(20 pcs)

Dimension



Model Name	Lamp Power (W)	A inch (mm)	B inch (mm)	C inch (mm)	B' inch (mm)	C' inch (mm)
ELS5 [color]K-120V	5	12.9/16" (319)	15/16" (24.3)	19/32" (32.7)	11/16" (27)	13/8" (35.5)
ELS10 [color]K-120V	10	22.13/16" (580)	15/16" (24.3)	19/32" (32.7)	11/16" (27)	13/8" (35.5)
ELS15 [color]K-120V	15	34.5/8" (880)	15/16" (24.3)	19/32" (32.7)	11/16" (27)	13/8" (35.5)
ELS20 [color]K-120V	20	46.7/16" (1180)	15/16" (24.3)	19/32" (32.7)	11/16" (27)	13/8" (35.5)

Accessories



Power cord

General type : (a) TUNPC120/XL | Vertical type : (b) TUNPC120/SM2/XL

(c) Connecting cable

TUNPTC/XL	TUNPTC1/XL	TUNPTC2/XL	TUNPTC4/XL	TUNPTC6/XL
150mm(6inch)	300mm(1feet)	600mm(2feet)	1200mm(4feet)	1800mm(6feet)

Connecting cable between hardwire box and fitting

(d) DSLTUNPTC/XL	ESLTUNPTC/XL	ESLTUNPTC1/XL	ESLTUNPTC2/XL	ESLTUNPTC4/XL	ESLTUNPTC6/XL
150mm(6inch)	300mm(1feet)	600mm(2feet)	1200mm(4feet)	1800mm(6feet)	

(e) Metal Hard wire box : MHWB-ESL

(f) Direct connector : TUNCPD

(g) End Cap : TUN-CAP

Mounting bracket

Normal bracket : (h) ELS-BRACKET/XL(A) 2pcs ELS-BRACKET/XL(B) 3pcs